

Motorola Canopy

2.4 GHz Backhaul Module 20 Mbps with Reflector



Description	2.4 GHz Backhaul Module 20 Mbps with Reflector
Canopy Part Number	2400BHRF20
Market Availability	North America, South America, Asia
Signaling Rate	20 Mbps
Typical LOS Range	35 mi (56 km)
Typical Aggregate Useful Throughput	14.0 Mbps
Frequency range of band	ISM 2400-2483.5 MHz
Non-overlapping Channels	3
Channel Width	20 MHz
Channel Spacing	every 2.5 MHz
Modulation Type	High Index 4-level Frequency Shift Keying (FSK) optimized for interference rejection
Encryption	DES capable
Latency	2.5 msec
Carrier to Interference ratio (C/I)	-3dB @ 10 Mbps, -10dB @ 20 Mbps at -65dBm
Nominal Receiver Sensitivity (dbm typical)	-79 dBm
Antenna Gain (dB)	8 dB
Reflector Gain	11 dB
EIRP (dB)	Adjustable
Equivalent Isotropic Radiated Power (EIRP)	Adjustable to 12.0 W
DC Power (typical)	0.34 A @ 24 VDC = 8.2 W
Antenna Beam Width	3 dB antenna beam width 17 degrees, Azimuth and Elevation
Mean Time Between Failure (MTBF)	40 yr
Temperature	-40° C to +55° C (-40° F to +131° F)
Wind Survival	190 km/hr (118 miles/hr)
Dimensions	Module: 11.75 in H x 3.4 in W x 3.4 in D (29.9 cm H x 8.6 cm W x 8.6 cm D). Passive Reflector: 18 inch H x 24 in W (45 cm H x 60 cm W)
Weight	.45 kg (1 lb), 3.0 kg (6.5 lbs) with passive reflector
Access Method	Time Division Duplex (TDD)
Interface	10/100 Base T, half/full duplex. Rate auto negotiated (802.3 compliant)
Protocols Used	IPV4, UDP, TCP, ICMP, Telnet, HTTP, FTP, SNMP
Network Management	HTTP, TELNET, FTP, SNMP Version 2c
FCC ID	ABZ89FC5808
Industry Canada Certification Number	109W-2400